AIYI Technologies

PORTABLE GAS DETECTOR

H2000





Version:1.1.2201



H2000 is portable 4 gas detector for LEL, O2, H2S, CO, gas type is customizable. Based on advanced sensor technology and IP66, it makes you more confident in harsh environments. You can check the alarm record on the detector.



PC+ABS+Rubber Drop Protection



Advanced Sensors Fast Response



Compact Design Easy to Go



Specifications

Description	H2000	
Function		
gas detected	CH4, O2, CO, toxic gas	
measure range	see QUICK-SELECTION-TABLE	
response time*	T90≤30/60/180S	
accuracy*	≤±5%FS	
repeatability*	≤2%FS	
sampling method	diffusion	
Electric		
battery	rechargeable Li-battery 1800mAh, nominal voltage 3.7V	
continuous operation	≥9h	
charging time	4-6h	
Alarm		
alarm method	sound,LED light,vibration	
sound intensity	≥90dB	
Display and Operation		
display	TFT Color display screen	
button	3 (UP, DOWN, ENTER)	
Environment		
ingress protection	IP66	
operating temperature* -20°C~60°C		
operating humidity 10~95%RH non-condensing		
operating pressure	80-120kPa	
Structure		
body material	PC+ABS	
weight	veight 200g	
dimensions	66X127X46mm	
Certificates		
EX	Exdib II CT4 Gb	

Note:* refers to there's some difference vary from different gas, please contact the manufacturer for details.

NO.	Gas	Measure range	Resolution
1	O2	0-25%VOL	0.1%VOL
2	CO	0-1000ppm	1ppm
3	H2S	0-100ppm	1ppm
4	SO2	0-20ppm	0.1ppm
5	H2	0-1000ppm	1ppm
6	CL2	0-10ppm	0.1ppm
7	NH3	0-100ppm	1ppm
8	HCL	0-30ppm	0.1ppm
9	NO	0-250ppm	1ppm
10	NO2	0-20ppm	0.1ppm
11	ETO	0-20ppm	0.1ppm
12	CH4	0~100%LEL	1%LEL

QUICK SELECTION TABLE -- GAS DETECTED

Note: 1, Any gas or measure range that not mentioned above, just contact AIYI Technologies for further information; 2, 1µmol/mol=1ppm



Disclaimer: All pictures, configurations and parameters in this document are for reference only. There may be differences with the actual products. Any difference is subject to the latest real products.

03